TOWN OF OKOTOKS

WASTEWATER SYSTEM

2018 ANNUAL REPORT





Approval # 1028-03-00

TABLE OF CONTENTS

1.	Wastewater System Introduction	3
2.	EPCOR Quality Assurance Program	3
3. BOD	Summary of WWTP Untreated Wastewater Influent: Monthly Summaries; /TSS/Volume; Approval 1028-03-00; Table 6-1	5
4. Amn	Summary of WWTP Untreated Wastewater Influent: Monthly Summaries; nonia/Total Phosphorus; Approval 1028-03-00; Table 6-1	7
5. BOD	Summary of WWTP Parameters: Treated Wastewater Effluent: Monthly Summaries; /CBOD/TSS/Volume; Approval 1028-03-00; Table 6-1	9
6. Amn	Summary of WWTP Parameters: Treated Wastewater Effluent: Monthly Summaries; nonia/Total Phosphorus/Acute Lethality; Approval 1028-03-00; Table 6-1	. 11
7. Nitro	Summary of WWTP Parameters: Treated Wastewater Effluent: Monthly Summaries; gen Analysis; Approval 1028-03-00;	. 13
8. Appı	Summary of WWTP Parameters: Total and Faecal Coliforms: Monthly Summaries; oval 1028-03-00; Table 6-1	. 15
9. Sum	Summary of WWTP Parameters: Sludge/Partially Composted Sludge: Monthly maries; Approval 1028-03-00; Table 6-1	. 17
10.	Chart – WWTP: Five Year Biosolids Production	. 18
11.	Summary of Incidents Reported to AEP – 2018	. 18
12.	Summary of Treated Wastewater used for Irrigation – 2018	. 18
13.	WWTP Uncommitted Hydraulic Reserve Capacity – 2018-2022	. 19
14.	Summary of Chemicals Used - 2018	. 20
15.	Summary of WSER Testing – 2018	. 21
16.	Summary of Operational Highlights & Problems	. 22
17.	Operator Certification	. 25
18.	Supervising Operator	. 26

1. Wastewater System Introduction

EPCOR Water Services have prepared the Water and Wastewater Annual reports on behalf of the Town of Okotoks. EPCOR and the Town of Okotoks have entered into an agreement to operate and maintain the wastewater system in Okotoks which commenced as of June 1st, 2005. The current wastewater treatment facility is a Level IV Tertiary BNR (biological nutrient removal) treatment process with continuous discharge to the Sheep River.

2. EPCOR Quality Assurance Program

The EPCOR Water Services Quality Assurance Program for external sites is intended to be part of a larger overall company Quality Management System which ensures that the utility:

- can demonstrate that it can consistently meet regulatory requirements
- can demonstrate that it can meet internal operational requirements
- can enhance customer protection through effective application of a quality system
- Continuously improves the overall quality system.

The EPCOR QA program is in place to ensure that water and wastewater quality data is reliable and technically (and legally) defensible, data is reported correctly, violations are reported in a timely manner, approval requirements are met, and water or wastewater quality problems are responded to effectively. For external and internal audit purposes EPCOR must be also be able to demonstrate that:

- it is doing what it says it is doing in all of its operations and it is has the documentation to back this claim up,
- data, and procedures for generating data, are verified by a qualified group that is independent of operations, and
- It is exercising due diligence by requiring that a reasonable level of quality assurance is in place at all external sites, and not only at the Edmonton operations.
- Has identified risks to the utility and has prepared remedial action plans for improvements.

An acceptable defined level of quality assurance on operational performance is specifically required by the EPCOR Risk Management Internal Audit.

Components of the External Sites QA Program

To satisfy these general requirements, the EPCOR Water Services Quality Assurance section will act as an auditor independent of operational management at each external site. The goal is to ensure that data is produced, recorded and reported in manners that are consistent with ISO 17025 requirements.

The components of the quality assurance program will include:

- 1. Initial QA assessments of new sites.
- 2. Ongoing routine site QA audits.
- 3. Preparation of audit reports and follow-up.
- 4. Analysis of EPCOR internal monthly Proficiency Testing (PT) samples.
- 5. Review of monthly and annual utility performance reports.
- 6. Tracking and review of site incident reports.
- 7. Development and review of site cross-connection control program (CCC).
- 8. Development and review of site watershed protection programs.
- 9. Training of operators at external sites on analytical procedures as required.

The plan and procedures will be reviewed regularly, at least on an annual basis, and amended as necessary.

3. Summary of WWTP Untreated Wastewater Influent: Monthly Summaries; BOD/TSS/Volume; Approval 1028-03-00; Table 6-1

				able 6-1: Mon stewater (Raw					er System	1		
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location		Jan	Feb	Mar	Apr	May	Jun	Jul
					MIN	353	328	343	226	237	244	230
BOD_5	mg/L	Once per day	Composite	Entering WWTP	MAX	573	638	660	612	452	594	504
					AVG	438	472	428	359	339	370	367
					MIN	280	288	260	160	152	176	152
TSS	mg/L	Once per day	Composite	Entering WWTP	MAX	432	600	448	420	448	416	476
					AVG	338	352	321	283	242	286	311
					MIN	6456	6314	3923	6406	7018	6778	6562
VOLUME	m ³ /day	Once per day	Continuous	Entering WWTP	MAX	7297	7188	7367	9084	8174	8557	9474
					AVG	6728	6606	6724	7536	7446	7267	7077
					TOTAL	208563	184957	208445	226071	230821	218007	219377

BOD5 - Biochemical Oxygen Demand

TSS - Total Suspended Solids

	Ap	proval # 1028 Untre		6-1: Monitori ater (Raw Inf					stem		
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location		Aug	Sep	Oct	Nov	Dec	Annual
					MIN	286	262	300	343	314	226
BOD_5	mg/L	Once per day	Composite	Entering WWTP	MAX	735	647	491	590	699	735
					AVG	409	420	391	436	453	407
					MIN	236	252	256	268	276	152
TSS	mg/L	Once per day	Composite	Entering WWTP	MAX	840	448	392	488	404	840
					AVG	347	327	320	324	326	315
					MIN	5896	6287	6308	6182	5986	3923
VOLUME	m ³ /day	Once per day	Continuous	Entering WWTP	MAX	6898	7379	7620	7343	7138	9474
					AVG	6507	6709	6734	6636	6492	6872
					TOTAL	201731	201259	208769	199090	201254	2508344

BOD5 - Biochemical Oxygen Demand TSS - Total Suspended Solids

4. Summary of WWTP Untreated Wastewater Influent: Monthly Summaries; Ammonia/Total Phosphorus; Approval 1028-03-00; Table 6-1

			1028-03-00; Ta ed Wastewater		Ü				•			
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location		Jan	Feb	Mar	Apr	May	Jun	Jul
					MIN	32.2	36.8	33.8	23.6	28.0	29.2	22.3
Ammonia - Nitrogen	mg/L	Once per week	Composite	Entering WWTP	MAX	44.8	40.6	42.6	40.9	34.8	37.5	35.2
					AVG	36.7	38.7	38.4	33.5	31.5	32.3	31.0
					MIN	5.85	6.20	6.35	5.65	5.65	4.85	4.50
Total Phosphorus	mg/L	Once per week	Composite	Entering WWTP	MAX	8.35	8.10	8.30	7.60	7.75	7.95	7.65
					AVG	7.19	7.29	7.21	6.54	6.24	6.35	6.24

	A		28-03-00; Table Wastewater (R					•			
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location		Aug	Sep	Oct	Nov	Dec	Annual
					MIN	31.6	35.5	33.3	31.7	32.5	22.3
Ammonia - Nitrogen	mg/L	Once per week	Composite	Entering WWTP	MAX	47.2	44.6	52.3	39.5	46.7	52.3
					AVG	35.2	39.1	37.2	35.6	36.6	35.5
					MIN	5.85	6.05	6.05	5.15	5.75	4.50
Total Phosphorus	mg/L	Once per week	Composite	Entering WWTP	MAX	12.10	8.10	8.50	8.50	8.85	12.10
					AVG	7.34	7.14	6.92	6.85	6.93	6.85

5. Summary of WWTP Parameters: Treated Wastewater Effluent: Monthly Summaries; BOD/CBOD/TSS/Volume; Approval 1028-03-00; Table 6-1

		Арр	oroval # 102	28-03-00; Ta Treated W		Ŭ							r S	ystem						
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location	Approval Limit		J	an		Feb]	Mar		Apr		May		Jun		Jul
						MIN	<	2.0	<	2.0		2.7		2.2		2.1	<	2.0	<	2.0
BOD_5	mg/L	Once per day	Composite	Prior to Release	N/A	MAX		4.6		5.2		12.2		11.0		5.9		7.3		5.3
MDL: 2 mg/L						AVG		2.9		3.3		5.6		5.1		3.4		4.2		3.0
						MIN	<	2.0	<	2.0	<	2.0	<	2.0	<	2.0	<	2.0	<	2.0
CBOD ₅	mg/L	Once per day	Composite	Prior to Release	≤ 20 mg/L	MAX		4.3		2.5		12.2		3.5		3.7		3.3		2.1
MDL : 2 mg/L						AVG		2.2		2.0		2.7		2.2		2.1		2.2		2.0
						MIN	<	2.5	<	2.5		2.5	<	2.5	<	2.5	<	2.5	<	2.5
TSS	mg/L	Once per day	Composite	Prior to Release	≤ 15 mg/L	MAX	<	2.5		2.6		4.7		4.3		3.6		3.6	<	2.5
MDL : 2.5 mg/L						AVG	<	2.5		2.5		3.6		2.8		2.6		2.7	<	2.5
						MIN		6102		5900		2239		5998		6685		6461		6157
VOLUME	m³/day	Once per day	Continuous	Prior to Release	N/A	MAX		6903		6861		7037		8920		7851		8169		9669
						AVG		6345		6285		6328		7252		7116		6922		6753
						TOTAL	1	96709		175973		196172		217563		220592		207666		209347

BOD₅ - Biochemical Oxygen Demand

< BOD5/CBOD5 Estimate : Difference between DO1 & DO5 < 2 mg/L

CBOD₅ - Carbonaceous Biochemical Oxygen Demand

< TSS Estimate: Less than 2.5 mg was retained on the filter

TSS - Total Suspended Solids

		Approva	l # 1028-03 Trea		6-1: Moni water: BO	U						ewater S	Sys	tem				
Parameter	Units of Measure	Frequency	Sample		Approval Limit			Aug		Sep		Oct		Nov		Dec		Annual
						MIN	<	2.0	<	2.0		2.0		2.0		2.4	<	2.0
BOD_5	mg/L	Once per day	Composite	Prior to Release	N/A	MAX		5.0		4.6		10.1		5.3		7.5		12.2
MDL: 2 mg/L						AVG		2.5		3.3		3.5		3.4		4.8		3.8
						MIN	<	2.0	<	2.0	<	2.0	\	2.0	<	2.0	<	2.0
CBOD ₅	mg/L	Once per day	Composite	Prior to Release	≤ 20 mg/L	MAX		2.3	<	2.0		4.0		2.2		3.4		12.2
MDL: 2 mg/L						AVG		2.0	<	2.0		2.1		2.0		2.4		2.2
						MIN	<	2.5	<	2.5	<	2.5	<	2.5	<	2.5	<	2.5
TSS	mg/L	Once per day	Composite	Prior to Release	≤ 15 mg/L	MAX	<	2.5		2.9		3.0	<	2.5		3.9		4.7
MDL : 2.5 mg/L						AVG	<	2.5		2.5		2.5	<	2.5		2.8		2.7
						MIN		5577		5757		5595		5500		5238		2239
VOLUME	m ³ /day	Once per day	Continuous	Prior to Release	N/A	MAX		6917		6733		6738		6536		6408		9669
						AVG		6193		6118		6054		5899		6021		6441
						TOTAL		191991		183540		187676		176965		186641		2350835

BOD₅ - Biochemical Oxygen Demand

< BOD5/CBOD5 Estimate : Difference between DO1 & DO5 < 2 mg/L

CBOD₅ - Carbonaceous Biochemical Oxygen Demand

< TSS Estimate: Less than 2.5 mg was retained on the filter

TSS - Total Suspended Solids

6. Summary of WWTP Parameters: Treated Wastewater Effluent: Monthly Summaries; Ammonia/Total Phosphorus/Acute Lethality; Approval 1028-03-00; Table 6-1

					Table 6-1: Moni MMONIA - TO	Ŭ			•				
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location	Approval Limit		Jan	Feb	Mar	Apr	May	Jun	Jul
					Oct 1 - Jun 30 ≤ 10 mg/L	MIN	< 0.50	< 0.50	1.48	0.61	< 0.50	< 0.50	< 0.50
Ammonia - Nitrogen	mg/L	Once per day	Composite	Prior to Release		MAX	1.26	6.20	6.51	4.48	1.17	< 0.50	< 0.50
MDL : 0.50 mg/L					Jul 1 - Sep 30 ≤ 5mg/L	AVG	0.54	2.13	3.77	1.99	0.52	< 0.50	< 0.50
						MIN	0.04	0.10	0.20	0.11	0.09	0.08	0.05
Total Phosphorus	mg/L	Once per day	Composite	Prior to Release	≤ 0.5 mg/L	MAX	0.19	0.22	0.37	0.23	0.22	0.27	0.18
MDL: 0.02 mg/L						AVG	0.14	0.17	0.28	0.18	0.17	0.19	0.12
Acute Lethality		Once											
Using Rainbow	LC50	every 3	Grab	Prior to Release	N/A			> 100			> 100		
Trout	%	months											

NOTE: All samples tested for Acute Lethality in 2018 are reported as > 100 (Not Acutely Lethal).

					6-1: Monitoring NIA - TOTAL I					•			
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location	Approval Limit			Aug	Sep	Oct	Nov	Dec	Annual
					Oct 1 - Jun 30 ≤ 10 mg/L	MIN	<	0.50	< 0.50	< 0.50	< 0.50	< 0.50	< 0.50
Ammonia - Nitrogen	mg/L	Once per day	Composite	Prior to Release		MAX	<	0.50	< 0.50	1.52	2.09	1.65	6.51
MDL: 0.50 mg/L					Jul 1 - Sep 30 ≤ 5mg/L	AVG	<	0.50	< 0.50	0.55	0.58	0.68	1.06
						MIN		0.10	0.07	0.15	0.02	0.07	0.02
Total Phosphorus	mg/L	Once per day	Composite	Prior to Release	≤ 0.5 mg/L	MAX		0.75	0.23	1.95	0.29	0.31	1.95
MDL : 0.02 mg/L						AVG		0.21	0.17	0.26	0.16	0.21	0.19
Acute Lethality		Once											AVG
Using Rainbow	LC50	every 3	Grab	Prior to Release	N/A		>	100			> 100		> 100
Trout	%	months											

NOTE: All samples tested for Acute Lethality in 2018 are reported as > 100 (Not Acutely Lethal).

7. Summary of WWTP Parameters: Treated Wastewater Effluent: Monthly Summaries; Nitrogen Analysis; Approval 1028-03-00;

		App			able 6-1: Mastewater: N		Ŭ			er System				
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location	Approval Limit		Jan	Feb	Mar	Apr	May	Jun		Jul
						MIN	1.10	2.41	4.38	2.07	0.70	1.39	<	0.07
TKN	mg/L	Once per week	Composite	Prior to Release	N/A	MAX	1.69	6.60	6.50	4.46	2.18	1.52		1.89
MDL: 0.07 mg/L						AVG	1.38	4.04	5.34	3.11	1.32	1.46		1.15
						MIN	5.12	5.02	4.45	4.53	4.64	5.13		5.27
NO ₂ - NO ₃	mg/L	Once per week	Composite	Prior to Release	N/A	MAX	5.65	5.49	5.10	5.10	5.27	5.38		5.65
MDL: 0.01 mg/L						AVG	5.39	5.27	4.83	4.84	5.01	5.28		5.53
						MIN	6.31	7.86	8.83	7.17	5.34	6.52		5.63
TN	mg/L	Once per week	N/A (calculated)	Prior to Release	≤ 15mg/L	MAX	7.10	11.62	11.22	9.30	7.24	6.90		7.51
MDL: 0.01 mg/L						AVG	6.77	9.30	10.17	7.95	6.33	6.74		6.41

TKN - Total Kjeldahl Nitrogen

NO₂ - NO₃ - Nitrite and Nitrate Nitrogen

TN - Total Nitrogen

		Approva			6-1: Monit vater: NITR	Ŭ			water Syst	em		
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location	Approval Limit		Aug	Sep	Oct	Nov	Dec	Annual
						MIN	1.12	1.09	0.69	1.30	1.30	< 0.07
TKN	mg/L	Once per week	Composite	Prior to Release	N/A	MAX	7.38	1.75	8.94	3.60	7.60	8.94
MDL: 0.07 mg/L						AVG	2.93	1.45	2.64	2.05	3.33	2.52
						MIN	5.60	6.05	6.49	5.84	5.63	4.45
NO ₂ - NO ₃	mg/L	Once per week	Composite	Prior to Release	N/A	MAX	6.03	6.73	7.31	13.30	12.90	13.30
MDL: 0.01 mg/L						AVG	5.83	6.45	6.91	9.54	9.55	6.20
						MIN	6.99	7.65	7.24	7.50	8.05	5.34
TN	mg/L	Once per week	N/A (calculated)	Prior to Release	≤ 15mg/L	MAX	13.38	8.44	15.92	16.50	20.20	20.20
MDL: 0.01 mg/L						AVG	8.76	7.89	9.53	11.58	12.88	8.68

TKN - Total Kjeldahl Nitrogen

NO₂ - NO₃ - Nitrite and Nitrate Nitrogen

TN - Total Nitrogen

8. Summary of WWTP Parameters: Total and Faecal Coliforms: Monthly Summaries; Approval 1028-03-00; Table 6-1

			Approva			1: Monitorin ter: TOTAL	_						ystei	m						
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location	Approval Limit		,	Jan		Feb		Mar		Apr]	May		Jun		Jul
Total	Count			Prior to	≤ 1000	MIN	<	10	<	10	<	10	<	10	<	10	<	10	<	10
Coliform	per	Once per week	Grab	Release	per 100 mL	MAX		20		20	<	10		10		10		20	<	10
	100 mL					Geometric Mean		11		12	<	10		10		10		12	<	10
Faecal	Count			Prior to	≤ 200	MIN	<	10	\	10	<	10	V	10	<	10	<	10	<	10
Coliform	per	Once per week	Grab	Release	per 100 mL	MAX		20		10	<	10		10	<	10	<	10	<	10
	100 mL					Geometric Mean		11		10	<	10		10	<	10	<	10	<	10

NOTE: Samples for coliform analysis are sent to the Provincial Health Lab on a weekly basis. Approval limit is based on the monthly geometric mean of weekly samples.


	Approval # 1028-03-00; Table 6-1: Monitoring - Town of Okotoks Wastewater System Treated Wastewater: TOTAL & FAECAL COLIFORMS																
Parameter	Units of Measure	Frequency	Sample Type	Sampling Location				Aug		Sep		Oct		Nov		Dec	Annual
Total	Count			Prior to	≤ 1000	MIN	<	10	<	10	<	10	<	10	<	10	10
Coliform	per	Once per week	Grab	Release	per 100 mL	MAX	<	10	<	10		20		10		600	600
	100 mL					Geometric Mean	<	10	<	10		13		10		59	15
Faecal	Count			Prior to	≤ 200	MIN	<	10	<	10	<	10	<	10	<	10	10
Coliform	per	Once per week	Grab	Release	per 100 mL	MAX	<	10	<	10		20	<	10		173	173
	100 mL					Geometric Mean	<	10	<	10		11	<	10		36	12

NOTE: Samples for coliform analysis are sent to the Provincial Health Lab on a weekly basis. Approval limit is based on the monthly geometric mean of weekly samples.

9. Summary of WWTP Parameters: Sludge/Partially Composted Sludge: Monthly Summaries; Approval 1028-03-00; Table 6-1

	EPCOR Water Services - Okotoks Wastewater Treatment Plant 2018 Annual Partially Composted Sludge Production MIN/MAX/AVG										
		COI	MPOST FI	EEDSTO	CK		SOLID	S SHIPPE	CD FROM		
	Dewatered Sludge TOTAL	Dewatered Sludge MIN	Dewatered Sludge MAX	Wood Shavings Total	Wood Shavings MIN	Wood Shavings MAX	Mixed Feedstock to Regional Facility TOTAL	Mixed Feedstock to Regional Facility - MIN	Mixed Feedstock to Regional Facility - MAX	Raw Screenings to Regional Landfill TOTAL	General Notes
Month			Metric Toni	nes/Month				Metric To	nnes/Month		1) Raw Screenings/Grit
JAN	328.8	7.1	15.7	139.8	3.4	6.3	468.6	10.5	21.9	7.5	hauled to landfill: kept separate
FEB	281.6	7.6	13.4	117.7	3.4	5.4	399.3	11.1	18.7	5.7	from Biosolids Compost.
MAR	280.0	0.0	14.2	117.5	0.0	5.6	397.4	0.0	19.7	6.2	
APR	368.8	7.7	21.0	164.8	3.4	9.2	533.7	11.1	30.2	8.2	2) All raw feedstock
MAY	324.9	7.3	15.7	136.1	3.4	6.8	461.0	10.8	22.5	7.5	(dewatered sludge & sawdust)
JUN	314.8	7.9	13.5	134.9	3.2	5.5	449.6	11.1	18.9	6.7	sent to approved regional compost
JUL	279.7	6.2	12.3	107.7	0.3	5.4	387.3	8.8	17.6	4.9	facility - EcoAg.
AUG	274.9	6.7	15.0	104.0	2.7	5.4	378.9	9.6	20.4	3.7	
SEP	253.2	5.8	11.7	100.9	1.9	4.7	354.1	8.0	16.2	5.2	3) Wood amendment supplied
OCT	288.5	4.3	14.6	110.1	1.6	6.2	398.6	5.9	20.7	7.9	by Spray Lakes Sawmills.
NOV	311.2	8.2	13.3	125.3	3.1	5.3	436.5	11.4	18.4	5.6	
DEC	309.6	8.0	16.0	125.7	3.1	6.4	435.2	11.1	22.4	4.9	
TOTAL	3615.9			1484.4			5100.3			74.1	
AVG	301.3			123.7			425.0			6.2	
MIN	253.2			100.9			354.1			3.7	
MAX	3615.9			164.8			533.7			8.2	WAS: Waste Activated Sludge

10. Chart - WWTP: Five Year Biosolids Production



11. Summary of Incidents Reported to AEP – 2018

Nov 26 – Operator was called into the WWTP at 5:45pm to find that the UV slide gate that controls the height of the Effluent in the UV channel had failed in the open position causing the UV lights to shut off due to the bulbs getting exposed. The system was off for three hours which is a contravention of the approval to operate forcing a call to AEP and reporting the issue. AEP REFERENCE # 347024

<u>July 10</u> – During a quality assurance review of the annual report (February, 2019), it was identified that the TKN result from July 10th was deemed to be invalid and should be reported to AEP as an invalid sample due to likely sample contamination. <u>AEP REFERENCE # 349678</u>

12. Summary of Treated Wastewater used for Irrigation – 2018

There was no treated wastewater used for irrigation purposes in 2018.

13. WWTP Uncommitted Hydraulic Reserve Capacity – 2018-2022

WWTP Uncommitted Hydraulic Reserve Capacity

Municipality	Town of	Okotoks	Fac	ility	Okotoks Wastewater Treatment Plant			
Supervising Operator	James M	I cElmon	Phon	e No.	(403) 899-6343			
Treatment Type	Mecha Tertiar	nical – y BNR	Design Cap	acity (m3/d)	10,000			
	Year	2018	*2019	*2020	*2021	*2022		
Average Daily Flow - 2018	m3/d	6,872	6,720	6,915	7,109	7,304		
Average Daily Flow Per Capita (F)	m3/capita/d	0.237	0.225	0.225	0.225	0.225		
Hydraulic Reserve Capacity (Cr)	m3/d	3,128	3,280	3,085	2,891	2,696		
Number of Unconnected Approved Lots (L)	lots	419	400	400	400	400		
Connected Population (P)	persons	29,002	29,867	30,732	31,597	32,462		
Number of Residential Connections (H)	connections	9,075	11,062	11,382	11,703	12,023		
Committed Reserve (Com)	m3/d	317	243	243	243	243		
Uncommitted Reserve Capacity (Cu)	m3/d	2,811	3,037	2,842	2,648	2,453		
Cr = Design Capacity – Average Daily Flow		*Years 2019-2022 are estimates only						
Cu = Cr - [L*F*P/H]	Future Pop is based on 5 yr annual ual avg growth rate of 865							
2018 connected Population is based on Federal census	data	Future Unconnected Approved Lots based on 5 yr avg						
		Future Res Connections is based on 2.7 people per connection						

14. Summary of Chemicals Used - 2018

	Summary of Chemicals Used in 2018										
MONTH	Zetag 8190 Dry Polymer kg	ALUM kg	Sodium Hypochlorite 16% L	Sodium Sulfite - Dechlorination tablets Kg							
Jan	536	0	0	0							
Feb	425	0	0	0							
Mar	446	0	20	1							
Apr	560	0	20	1							
May	543	0	0	0							
Jun	612	0	20	1							
Jul	540	0	0	0							
Aug	472	0	0	0							
Sep	449	0	0	0							
Oct	484	0	60	3							
Nov	511	0	0	0							
Dec	521	0	0	0							
TOTAL	6098	0	120	6							

¹ Dry Polymer used in Sludge Dewatering process

² Sodium Hypochlorite used for cleaning Disk Filtration process (Not for Treatment)

³ Sodium Sulfite used for dechlorination after disk filter cleaning

 $_{\rm 4}\,$ Alum used for Chemical Phosphorus removal (No Alum was used in 2018)

15. Summary of WSER Testing – 2018

WSER Monitoring Requirements 2018 - Town of Okotoks WWTP											
Sample Type		2		ameter ur Composit	te		Grab				
Parameter	CBOD			TSS		Total Ammonia	Acute Lethality				
Environment Canada Limits	< 0r >	< 25 mg/L	< 0r >	< 25 mg/L	< 0r >		<50%				
Date 9-Jan-18		4	_	2	Ť	0.07					
23-Jan-18	<	4	<	1		0.07					
6-Feb-18	<	4		2		0.58	Feb 5/2018				
20-Feb-18	<	4	<	2		3.44	100%				
6-Mar-18	<	4		4		4.60					
20-Mar-18	<	4		3		3.62					
04 AVC		4		2		2.07					
Q1 AVG Q1 MIN	<	4	_	<u>2</u> 1		2.07 0.07					
Q1 MAX	<	4	<	4		4.60					
QT WAX	È	7		7		4.00					
3-Apr-18	<	4		5		1.70					
17-Apr-18	<	4		3		2.42					
1-May-18	<	4	<	1		0.68	May 22/2018				
15-May-18	<	4		13		0.09	100%				
29-May-18	<	4	<	2		0.03					
12-Jun-18	<	4		3		0.05					
26-Jun-18	<	4		7		0.10					
Q2 AVG	<	4		5		0.72					
Q2 MIN	<	4	<	1		0.03					
Q2 MAX	<	4		13		2.42					
40 hd 40		4		2		0.04					
10-Jul-18 24-Jul-18	<	4	<	2		0.04 0.11					
7-Aug-18	<	4	<i>'</i>	2		0.11	Aug 17/2018				
21-Aug-18	<	4	<	2		0.05	100%				
4-Sep-18	<	4	<	2		0.05	10070				
18-Sep-18	<	4		4		0.04					
Q3 AVG	<	4		2		0.05					
Q3 MIN	<	4	<	2		0.04					
Q3 MAX	<	4		4		0.11					
2-Oct-18	<	4		35		0.03					
16-Oct-18	<	4	<	2		0.07					
30-Oct-18	<	4	<	2		0.09					
13-Nov-18	<	4	<	2		0.10	Nov 22/2018				
27-Nov-18	<	4	<	2		0.10	100%				
11-Dec-18	<	4		2		0.41					
25-Dec-18	<	4	<	2		1.33					
Q4 AVG		4		7		0.30					
Q4 AVG Q4 MIN	<	4	<	2		0.03					
Q4 MAX	~	4	\vdash	35		1.33					
Annual AVG Annual MIN	<	4	<	1		0.79 0.03					

16. Summary of Operational Highlights & Problems

January 2018

- Jan 3 Southern Alberta maintenance (SAM) replaced the backwash pump on Disc Filter #3 due to a motor failure.
- **Jan 4** Operations was able to get the Odour Control system thawed out and placed back into service due to the below average cold external temperatures we are experiencing.
- Jan 9 New rotor and stator was installed on sludge feed pump #1. (Centrifuge)
- Jan 12 During daily WWTP inspections it was found that the Grit Vortex discharge piping had froze solid and needed High Country Vac services to come onsite and steam the line to free blockage.

February 2018

- Feb. 13 Operations called in afterhours due to a DAF unit communication failure that had to be reset and placed back into service.
- **Feb. 21 –** Operations increased the WAS rate from 300 to 320 L/min due to a increase of the Secondary sludge blanket 5ft.
- **Feb. 28 –** Operations called in afterhours due to a Influent sampler fault that was found to be a blockage on the suction line that had to be removed.

March 2018

- Mar. 1 Operations increased wasting from Primary Clarifier to 34 m³ due to a 6 foot sludge blanket.
- Mar. 17 Operations was forced to shut down Screw pump #3 due to the bottom bearing failing.
- Mar. 23 Screw pump #1 had to be shut down due to a internal mechanical failure with the top weld.
- Mar. 23 Centrifuge went down on a programing issue forcing operations to transfer the contents of the Twas tank to the emergency holding cell until repairs were complete.
- Mar. 28 Operations with the help of SAM (Southern Alberta Maintenance) fixed the issue with the Centrifuge and returned it back into operation.
- Mar. 30 Operations increased WAS rate from 220 L/min to 250 L/min due to a increase in MLSS in aerobic zone #3.
- Mar. 31 The DAF unit was offline for 4 hours today while operators and (SAM) worked to repair a broken top drive chain that controls the top skimmer blades.

April 2018

- April 5 Screw pump #1 placed back into service after some major welding repairs were needed to repair stress fractures on the top half of screw pump.
- April 17 Northern underwater services (divers) onsite to do a scheduled inspection of the Secondary rake mechanism to determine if there was any further damage taking place, no further damage was found at this time.
- April 30 Operations cleaned off all three Bioreactor DO probes due to values out of range from a manual test done of the DO levels.

May 2018

- May 3 Operations installed a new motor and gearbox on the shaft less screw auger that's located in the solids handling building.
- May 15 High Country Vac services onsite to clean and remove the contents of the grease pit attached to the Primary Clarifier and haul it to Calgary for disposal.
- May 15 On call operator called after hours due to Air Blower #2 faulting out on high temperatures.
- May 17 RAS rate increased from 130 L/sec to 150 L/sec due to a high Secondary sludge blanket.
- May 23 Operations performed a routine cleaning and inspection of all three DO sensors in the Bioreactor.
- May 28 Screw Pump #2 was placed out of service due to the top bearing assembly failing.

June 2018

- June 1 Increased WAS rate from 280 L/min to 300 L/min due to high MLSS in the Bioreactor.
- June 4 Balzers contracting onsite to remove Screw Pump #2 and replace bottom bearing.
- **June 6 –** DAF unit was shut down for the 5 year annual inspection of the pressure tank and placed back into service after passing its inspection.
- **June 20** Placed Channel Monster out of service and removed from Influent channel due to right side cutter stack bearing failure and sent out to be repaired.
- **June 21 –** Balzers contracting back onsite to install new bottom bearing on Screw Pump #3 and place back into to service.
- June 27 Disc Filter #3 was taken off-line for a 48 hour cleaning after inspection of the filters.
- June 29 Dechlorinated Disc Filter #3 and placed back into service.

July 2018

- **July 2 –** WAS pump #1 faulted out and it was determined that the VFD was to blame for the issue, operations switched pump #1 over to WAS pump #2 VFD drive and placed into service.
- July 3 Operations removed blockage from Primary pump #1 and returned back into service.
- July 10 Weekly TKN sample deemed to be 'invalid' due to likely sample contamination. Reported
 to AEP following QA review of the annual report. AEP REFERENCE # 349678
- July 16 High Country Vac services on site to deal with a blockage in the Primary waste line.

August 2018

- Aug 17 Decreased primary clarifier wasting from 40m3 to 36m3 to increase sludge blanket for VFA production.
- Aug 17 Decreased wasting (WAS) from the bioreactor to increase SVI in the mixed liquor.
- Aug 17 Replaced all air filters on the blowers.
- Aug 27 Lowered primary wasting from 40m3 to 37m3 to increase primary blanket for VFA production.
- Aug 29 Removed mixer #3 from bioreactor due to failure and replaced with shelf spare.

September 2018

- **Sept 5** Operations lowered primary wasting down from 37 m³ to 35 m³ due to a two foot sludge blanket in the secondary clarifier.
- **Sept 23 –** Operations turned on air blower #4 in the afternoon due to low DO's in the bioreactor because of high Influent flows coming into the plant.

October 2018

- Oct 9 Lowered wasting rate from 275 L/min to 200 L/min from the Secondary to the DAF unit due to overloading issues with the DAF unit.
- Oct 13 Placed Disc Filter #2 off-line for cleaning due to the filter not being able to maintain weekend flow rates (by-passing).
- Oct 15 Took DAF unit off-line for 2 hours to do a complete drain down of tank and a flush of the saturation tank due to the DAF unit continually failing.
- Oct 17 Operations placed Disc Filter #2 back on-line after performing a 48 hour cleaning.
- Oct 22 Endress+Hauser with the help of (SAM) performed the annual Influent and Effluent mag meter calibrations.
- Oct 23 Canadian Underwater (divers) on-site today to perform the quarterly inspection of the Secondary rake mechanism and was found to be no change from previous dive.
- Oct 23 Operations placed Disc Filter #3 back on-line after performing a 24 hour cleaning.
- Oct 24 High Country Vac services and O'Leary construction on-site to repair a air leak from air blower #4 discharge line.
- Oct 30 SAM (southern Alberta maintenance) started the process of changing the air blower set points and daily DO requirements for the Bioreactor in efforts to lower air supply amount.

November 2018

- Nov 19 Operations unable to run denitrification pump for the bioreactor due to a pump and VFD failure. Operations were forced to transfer MLSS via 6 inch diesel pump overland to help with the denitrification process until the pump can be repaired.
- Nov 26 Operator was called into the WWTP at 5:45pm to find that the UV slide gate that controls
 the height of the Effluent in the UV channel had failed in the open position causing the UV lights to
 shut off due to the bulbs getting exposed. The system was off for three hours which is a
 contravention of the approval to operate forcing a call to AEP and reporting the issue. AEP
 REFERENCE # 347024
- Nov 28 Operations increased RAS rate to 100% from 90% to assist with denitrification due to main pump not working.

December 2018

- Dec 2 Decreased wasting from the bioreactor from 300 L/min to 275 L/min due to a sudden drop
 in MLSS test results.
- Dec 11 Operations took Flow EQ tank offline for a couple of days to determine if the return flow
 was affecting the Influent flow meter daily totals. After a few days offline it was found that the EQ
 flow was giving us a false read for Influent flow totals forcing the SCADA team to reprogram the
 daily totals to be more representative of the actual flows.
- Dec 18 The repaired Denitrification pump was installed and placed back into service.
- Dec 22 Suntech electrical onsite to perform final programing and testing on new Denitrification pump VFD.
- Dec 27 High Country Vac services onsite to clean out Primary grease line and pit due to issues with the system plugging off.

17. Operator Certification

As required under section 4.2 of Approval No. 1028-03-00, the wastewater treatment facility is classified as **Class IV** and the wastewater collection system is classified as **Class III**. The facilities are classified in accordance with the *Water and Wastewater Operators' Certification Guidelines*.

As per approval section 4.2.2(b), the operation of the wastewater treatment facility shall be performed by, or under the direction of:

- a) One operator who holds a valid Level IV (or higher) WWT (Wastewater Treatment) Operators Certificate of qualification; and
- b) Two operators each with a valid Level III (or higher) WWT Operators Certificate, and
- c) One operator with a Level II WWT (or higher) certificate, in charge of each of each shift

As per approval section 4.2.2(a), the operation of the wastewater collection system shall be performed by, or under the direction of:

- a) An operator who holds a valid Level III (or higher) WWC (wastewater collection) Operators Certificate; and
- b) At least one other operator who holds a valid Level II (or higher) WWC Operators Certificate
- The EPCOR operators in Okotoks are certified as shown within the table below:

Name	Position	Wastewater Treatment	Wastewater Collection	Cert. Number
Davey Robertson	Site Manager	Level 4	Level 2	2350
Pacer Wilson	Lead Hand	Level 2	Level 3	2956
Corey Hodgson	Lead Hand	Level 1	Level 3	2529
James McElmon	Lead Hand	Level 4	Level 2	4045
Johnathan Bartisch	Operator	Level 4	Level 2	2944
Jordan Ballard	Operator	Level 3	Level 1	3714
Terry Sapsford	Operator	Level 3	Level 2	4318
Doug Farough	Operator	Level 2	Level 3	3852
Marlon Anthony	Operator	Level 2	Level 1	4944
Bryan Steed	Operator	Level 1	Level 3	2292
Patti Kjinserdahl	Operator	N/A	Level 2	2429
Prakash Kattel	Operator	N/A	Level 1	5703

Site Manager Contact Information:

Davey Robertson Site Manager – Okotoks Operations EPCOR Utilities Inc.

200 – 1118 North Railway Street Okotoks, AB T1S 1K1

Bus: (403) 938-1230 ext. 5 Cell: (403) 899-6341

Email: drobertson@epcor.com

Supervising Operator Contact Information:

James McElmon Lead Hand – Okotoks WWT Operations EPCOR Utilities Inc.

200 - 1118 North Railway Street

Okotoks, AB T1S 1K1 Bus: (403) 938-1230 ext. 6 Cell: (403) 899-9343

Email: jmcelmon@epcor.com

18. Supervising Operator

Su La	James McElmon	4045
Signature	Printed	Certificate #